

大容量積層セラミックコンデンサ在庫表

定格電圧	温度特性	静電容量 (μ F)	製品番号	梱包数 (リール)
1608サイズ				
25v	BJ/X7R	0.022	TMK107BJ223KA-T	4,000
16V	BJ/X7R	0.033	EMK107BJ333KA-T	4,000
16V	BJ/X7R	0.047	EMK107BJ473KA-T	4,000
16V	BJ/X7R	0.068	EMK107BJ683KA-T	4,000
25V	BJ/X7R	0.1	TMK107BJ104KA-T	4,000
10V	BJ/X5R	0.15	LMK107BJ154KA-T	4,000
10V	BJ/X5R	0.22	LMK107BJ224KA-T	4,000
10V	BJ/X5R	0.33	LMK107BJ334KA-T	4,000
10V	BJ/X5R	0.47	LMK107BJ474KA-T	4,000
10V	BJ/X5R	0.68	LMK107BJ684KA-T	4,000
6.3V	BJ/X5R	1	JMK107BJ105KA-T	4,000
6.3V	BJ/X5R	3.3	JMK107BJ335KA-T	4,000
16V	F/Y5V	0.22	EMK107F224ZA-T	4,000
16V	F/Y5V	0.47	EMK107F474ZA-T	4,000
10V	F/Y5V	1	LMK107F105ZA-T	4,000
2012サイズ				
50V	BJ/X7R	0.022	UMK212BJ223KD-T	4,000
50V	BJ/X7R	0.033	UMK212BJ333KD-T	4,000
50V	BJ/X7R	0.047	UMK212BJ473KG-T	3,000
50V	BJ/X7R	0.068	UMK212BJ683KG-T	3,000
50V	BJ/X7R	0.1	UMK212BJ104KG-T	3,000
50V	BJ/X7R	0.15	UMK212BJ154KG-T	3,000
16V	BJ/X7R	0.22	EMK212BJ224KG-T	3,000
16V	BJ/X7R	0.33	EMK212BJ334KG-T	3,000
16V	BJ/X7R	0.47	EMK212BJ474KG-T	3,000
16V	BJ/X7R	0.68	EMK212BJ684KG-T	3,000
16V	BJ/X5R	1	EMK212BJ105KG-T	3,000
10V	BJ/X5R	2.2	LMK212BJ225KG-T	3,000
50V	F/Y5V	0.47	UMK212F474ZG-T	3,000
50V	F/Y5V	1	UMK212F105ZG-T	3,000
16V	F/Y5V	2.2	EMK212F225ZG-T	3,000
3216サイズ				
50V	BJ/X7R	0.15	UMK316BJ154KF-T	3,000
50V	BJ/X7R	0.22	UMK316BJ224KL-T	2,000
16V	BJ/X7R	0.47	TMK316BJ474KL-T	2,000
25V	BJ/X7R	0.68	TMK316BJ684KL-T	2,000
25V	BJ/X7R	1	TMK316BJ105KL-T	2,000
16V	BJ/X7R	2.2	EMK316BJ225ML-T	2,000
16V	BJ/X5R	4.7	EMK316BJ475ML-T	2,000
50V	F/Y5V	2.2	UMK316F225ZG-T	3,000
25V	F/Y5V	4.7	TMK316F475ZG-T	3,000
10V	F/Y5V	10	LMK316F106ZL-T	2,000

一般積層セラミックコンデンサ(温度保証用・Class 1)在庫表

形状寸法(EIA)	定格電圧	温度特性	公称静電容量 (pF)	形名	梱包数 (リール)
1.6 x 0.8 (0603)	50V	CK	0.5	UMK107CK0R5CZ-T	4,000
1.6 x 0.8 (0603)	50V	CK	1	UMK107CK010CZ-T	4,000
1.6 x 0.8 (0603)	50V	CK	1.5	UMK107CK1R5CZ-T	4,000
1.6 x 0.8 (0603)	50V	CK	2	UMK107CK020CZ-T	4,000
1.6 x 0.8 (0603)	50V	CJ	3	UMK107CJ030CZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	4	UMK107CH040CZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	5	UMK107CH050CZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	6	UMK107CH060DZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	7	UMK107CH070DZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	8	UMK107CH080DZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	9	UMK107CH090DZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	10	UMK107CH100DZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	12	UMK107CH120JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	15	UMK107CH150JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	18	UMK107CH180JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	22	UMK107CH220JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	27	UMK107CH270JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	33	UMK107CH330JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	39	UMK107CH390JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	47	UMK107CH470JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	56	UMK107CH560JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	68	UMK107CH680JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	82	UMK107CH820JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	100	UMK107CH101JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	120	UMK107CH121JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	150	UMK107CH151JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	180	UMK107CH181JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	220	UMK107CH221JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	270	UMK107CH271JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	330	UMK107CH331JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	390	UMK107CH391JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	470	UMK107CH471JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	560	UMK107CH561JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	680	UMK107CH681JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	820	UMK107CH821JZ-T	4,000
1.6 x 0.8 (0603)	50V	CH	1000	UMK107CH102JZ-T	4,000

一般積層セラミックコンデンサ(温度保証用・Class 2)在庫表

形状寸法(EIA)	定格電圧	温度特性	公称静電容量 (pF)	形名	梱包数 (リール)
1.6 x 0.8 (0603)	50V	BJ/X7R	1,000	UMK107B102KZ-T	4,000
1.6 x 0.8 (0603)	50V	BJ/X7R	1,500	UMK107B152KZ-T	4,000
1.6 x 0.8 (0603)	50V	BJ/X7R	2,200	UMK107B222KZ-T	4,000
1.6 x 0.8 (0603)	50V	BJ/X7R	3,300	UMK107B332KZ-T	4,000
1.6 x 0.8 (0603)	50V	BJ/X7R	4,700	UMK107B472KZ-T	4,000
1.6 x 0.8 (0603)	50V	BJ/X7R	6,800	UMK107B682KZ-T	4,000
1.6 x 0.8 (0603)	50V	BJ/X7R	10,000	UMK107B103KZ-T	4,000
1.6 x 0.8 (0603)	25V	BJ/X7R	15,000	TMK107B153KZ-T	4,000
1.6 x 0.8 (0603)	25V	F/Y5V	47,000	TMK107F473ZZ-T	4,000
1.6 x 0.8 (0603)	25V	F/Y5V	100,000	TMK107F104ZZ-T	4,000